




1

2

3

4

5



TECHNICAL CHARACTERISTICS

MATERIAL
INSULATOR: PA6/66
FLAMMABILITY RATING: UL94V0
COLOR: GREEN

ENVIRONMENTAL
OPERATING TEMPERATURE: -30°C UP TO +120°C
COMPLIANCE: LEAD FREE AND ROHS

MECHANICAL
FUSE-LINK: 5x20 mm

PACKAGING
BOX

A

B

C

RoHS Compliant

PROJECTION:



GENERAL TOLERANCE

±0,1



WÜRTH ELEKTRONIK

APPROVAL: QL

UNIT: MM

DESCRIPTION: ACCESSORIES - PCB - CLIP COVER - THT - WR-FSH

SIZE

AK

SCALE:

WERI PART NO: 696 122 003 001

A4

BY

SHEET: 1/2

DATE

DRAW: AK

FILE

11-SEP-14

PDF

AK

BY

DRAW: AK

FILE

DATE

FILE

BY

D

1

2

3

4

5

Cautions and Warnings:

This electronic component is designed and developed with the intention for use in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Würth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

A

B

C

RoHS Compliant

G				PROJECTION: 	GENERAL TOLERANCE .X = +/- 0.2 .XX = +/- 0.15		
F							
E							
D							
C				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE A4
B					SCALE:		
A	10-SEP-14	PDF	QL		SHEET: 2/2	WERI PART NO: DISCLAIMER	
REV	DATE	FILE	BY		DRAW: QL		

D