



SECTION J-J

- NOTES:
- 1- 20 CIRCUIT SIZE SHOWN FOR ILLUSTRATION PURPOSES.
  - 2- PIN PUSHOUT FORCE: (17.79 N)/4 LBS.
  - 3- PINS MUST MEET SOLDERABILITY SPEC. MIL-STD-202 METHOD 208B.
  - 4- WINDOW NOT AVAILABLE ON 6 AND 8 CIRCUIT SIZE.
  - 5- FOR CHARTED DIMENSIONS AND ASSEMBLY NO.S NOT SHOWN ON THIS SHEET - SEE SHEET 2.
  - 6- ROW TO ROW PIN HEIGHT VARIATION MUST NOT EXCEED (0.13)/.005 IN.
  - 7- PRODUCT CONFORMS TO PS-8723.

CKT.	8723				
	DIM. 'A'	DIM. 'B'	DIM. 'C'	DIM. 'D'	DIM. 'E'
06	(1.68) .066	(8.43) .332	(5.08) .200	(1.68) .066	
08	(1.68) .066	(10.97) .432	(7.62) .300	(1.68) .066	
10	(1.68) .066	(13.51) .532	(10.16) .400	(4.22) .166	
12	(1.68) .066	(16.05) .632	(12.70) .500	(4.22) .166	
14	(1.68) .066	(18.59) .732	(15.24) .600	(6.76) .266	
16	(1.68) .066	(21.13) .832	(17.78) .700	(6.76) .266	
18	(1.68) .066	(23.67) .932	(20.32) .800	(9.30) .366	
20	(1.68) .066	(26.21) 1.032	(22.86) .900	(1.68) .066	(19.46) .766
22	(1.68) .066	(28.75) 1.132	(25.40) 1.000	(1.68) .066	(22.00) .866
24	(1.68) .066	(31.29) 1.232	(27.94) 1.100	(1.68) .066	(24.54) .966
26	(1.68) .066	(33.83) 1.332	(30.48) 1.200	(1.68) .066	(27.08) 1.066
28	(1.68) .066	(36.37) 1.432	(33.02) 1.300	(1.68) .066	(29.62) 1.166
30	(1.68) .066	(38.91) 1.532	(35.56) 1.400	(1.68) .066	(32.16) 1.266
32	(1.68) .066	(41.45) 1.632	(38.10) 1.500	(1.68) .066	(34.70) 1.366
34	(1.68) .066	(43.99) 1.732	(40.64) 1.600	(1.68) .066	(37.24) 1.466
36	(1.68) .066	(46.53) 1.832	(43.18) 1.700	(1.68) .066	(39.78) 1.566
38	(1.68) .066	(49.07) 1.932	(45.72) 1.800	(1.68) .066	(42.32) 1.666
40	(1.68) .066	(51.61) 2.032	(48.26) 1.900	(1.68) .066	(44.86) 1.766
42	(1.68) .066	(54.15) 2.132	(50.80) 2.000	(1.68) .066	(47.40) 1.866
44	(1.68) .066	(56.69) 2.232	(53.34) 2.100	(1.68) .066	(49.94) 1.966
46	(1.68) .066	(59.23) 2.332	(55.88) 2.200	(1.68) .066	(52.48) 2.066
48	(1.68) .066	(61.77) 2.432	(58.42) 2.300	(1.68) .066	(55.02) 2.166
50	(1.68) .066	(64.31) 2.532	(60.96) 2.400	(1.68) .066	(57.56) 2.266
52	(1.68) .066	(66.85) 2.632	(63.50) 2.500	(1.68) .066	(60.10) 2.366
54	(1.68) .066	(69.39) 2.732	(66.04) 2.600	(1.68) .066	(62.64) 2.466
56	(1.68) .066	(71.93) 2.832	(68.58) 2.700	(1.68) .066	(65.18) 2.566
58	(1.68) .066	(74.47) 2.932	(71.12) 2.800	(1.68) .066	(67.72) 2.666
60	(1.68) .066	(77.01) 3.032	(73.66) 2.900	(1.68) .066	(70.26) 2.766
62	(1.68) .066	(79.55) 3.132	(76.20) 3.000	(1.68) .066	(72.80) 2.866
64	(1.68) .066	(82.09) 3.232	(78.74) 3.100	(1.68) .066	(75.34) 2.966
66	(1.68) .066	(84.63) 3.332	(81.28) 3.200	(1.68) .066	(77.88) 3.066
68	(1.68) .066	(87.17) 3.432	(83.82) 3.300	(1.68) .066	(80.42) 3.166
70	(1.68) .066	(89.71) 3.532	(86.36) 3.400	(1.68) .066	(82.96) 3.266
72	(1.68) .066	(92.25) 3.632	(88.90) 3.500	(1.68) .066	(85.50) 3.366

MATERIAL:

SHROUDED WAFER: GLASS FILLED POLYESTER, 94V-0; COLOR: BLACK.  
PINS: PHOSPHOR BRONZE, SEE SHEET 2 FOR FINISHES.

ASSEMBLY STYLE "A" AND "B"

DIMENSIONS SHOWN METRIC/INCH		UNLESS OTHERWISE SPECIFIED	SCALE 4:1
MILL	INCH	METRIC	
1 MILK ± .005	---	---	
2 MILK ± .01	± 0.13		
1 MILK ---	± 0.25		
DATE: _____		REV. _____	SCALE 4:1
DATE: _____	REV. _____	SCALE 4:1	

- U ADD -3803 OPT DCP2804-2268 DMORGAN 04/05/20
- T LEAD FREE U32804-1770 R WHITE 04/04/26
- S ADD -3802 OPTN ECR \*R22804-022 DMORGAN 04/01/2
- R2 TAB DIF DIM 6 CIR ECR \*R22804-0145 DMORGAN 56/09/01
- R1 ADD WDG LATCH NOTE ECR \*R22804-0399 DMORGAN 56/06/23
- R ADDED SHEET 7 PER ECR NO US8208 03-23-96
- O REMOVE FDP NO.S PER ECR NO US8205 05-15-94 B.S.
- P CHGD WINDOW NOTES PER ECR NO US30316 05-04-93 B.S.
- S O CHANGED MATERIAL PER ECR NO US3046 01-22-93 B.S.
- R2 R REVISD A REDRAWN PER ECR NO US2873 05-29-92 B.S.
- L NTR REVISIONS

DATE: _____	REV. _____	SCALE 4:1	
DATE: _____	REV. _____	SCALE 4:1	

