

Specification Sheet

Part Number: CTM30C2



Cable Tie Anchor Mount, .86" x .61", .2" Hole Dia, .31" Max Tie Width, PA66, Black, 100/pkg

| | |
|--------------------------------|---|
| Article Number | 151-30600 |
| Type | CTM3 |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">• Designed for use with 18 through 120 pound cable ties to provide stability when securing bundles.• Secures with a single screw providing quick installation. |
| Quantity Per | bag |
| Product Description | HellermannTyton cable tie mounts are designed for use with 18 through 120 pound cable ties to provide stability when securing bundles. The mounts are installed quick and easy by securing a single screw. |
| Short Description | Cable Tie Anchor Mount, .86" x .61", .2" Hole Dia, .31" Max Tie Width, PA66, Black, 100/pkg |

Global Part Name

CTM3-PA66-BK

Length L (Imperial)

0.86

Length L (Metric)

21.8

Fixation Method

Screw Mounting and Rivet

Width W (Imperial)

0.61

Width W (Metric)

15.5

Cable Ties

T18 - T120

Height H (Imperial)

.37

Height H (Metric)

9.40

Cable Tie Width Max (Imperial)

0.31

Cable Tie Width Max (Metric)

7.9

Mounting Hole Diameter D (Imperial)

0.2

Mounting Hole Diameter D (Metric)

5.1 mm

Mounting Hole Diameter D Max (Metric)

5.1

Material

Polyamide 6.6 (PA66)

| | |
|--|--|
| Material Shortcut | PA66 |
| Flammability | UL 94 V2 |
| Operating Temperature (Metric) | -40°F to +185°F (-40°C to +85°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| Certification/Specification WEB | UL ANSI/UL 62275 UL ANSI/UL 746B UL ANSI/UL 1565 |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |
| Package Quantity(Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909987 |
| Content Unit(BMEcat) | pcs. |
| Weight (Metric) | 1 |