APPLICAI	BLE STAN	DARD										
OPERATING		DE DANCE				STORAGE		<u></u>	-10 °C TO 60 °C (2)			
RATING	TEMPERATURE RANGE				OPE	PERATURE RANGE RATING HUMIDITY						
	VOLTAGE CURRENT		125 V AC		RAN STO		UMIDITY		40 % TO 80 %)		
			0.5 A RAN			IGE 60 % MAX ⁽²⁾						
			SPEC		ATION	<u>IS</u>				,		
	EM		TEST METHOD	l			RI	EQUI	REMENTS	QT	AT	
CONSTRU		1,40,141				1.000	20110		414/14/0			
GENERAL EX	XAMINATION		VISUALLY AND BY MEASURING INSTRUMENT. CONFIRMED VISUALLY.				RDING	IO DR	AWING.	×	×	
ELECTRIC	CHARAC											
CONTACT R			100 mA (DC OR 1000 Hz).				45 mΩ MAX .					
CONTACT RESISTANCE		20 mV MAX, 1 mA(DC OR 1000Hz)				55 mΩ MAX .				×		
MILLIVOLT LEVEL METHOD		,										
INSULATION RESISTANCE		250 V DC				100 MΩ MIN.				×		
VOLTAGE PROOF		300 V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.				×		
MECHANI										1		
INSERTION A			RED BY APPLICABLE CONN	IECTOR		INSER	TION FO	DRCE:	17.6 N MAX.			
WITHDRAWAL FORCES						WITHDRAWAL FORCE: 2.0 N MIN.				×		
MECHANICAL OPERATION		300 TIMES INSERTIONS AND EXTRACTIONS.				 CONTACT RESISTANCE: 55 mΩ MAX. NO DAMAGE, CRACK AND LOOSENESS OF PARTS. 				×		
VIBRATION		FREQUENCY 10 TO 55 Hz,							DISCONTINUITY OF	×		
			AMPLITUDE: 1.52 mm,				1 μs.					
SHOCK		AT 2 h FOR 3 DIRECTIONS. 490 m/s ² , DURATION OF PULSE 11 ms				② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×		
SHOOK			TIMES FOR 3 DIRECT		IIIS	OF	PARIS.			^		
ENVIRON	MENTAL C	HARAC	TERISTICS									
DAMP HEAT		EXPOSE	EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.				NTACT	RESIS	TANCE: 55 mΩ MAX.	×		
(STEADY STATE)						-			SISTANCE:100 M Ω MIN.			
RAPID CHANGE OF TEMPERATURE		TEMPERATURE-55 \rightarrow +15 \sim +35 \rightarrow +85 \rightarrow +15 \sim +35 $^{\circ}$ C TIME 30 \rightarrow 10 $^{\circ}$ 15 \rightarrow 30 \rightarrow 10 $^{\circ}$ 15 min UNDER 5 CYCLES.				③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×		
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.				① CONTACT RESISTANCE: 55 mΩ MAX.② NO HEAVY CORROSION.				×		
HYDROGEN SULPHIDE		EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA 38)								×		
RESISTANCE TO		1)REFLC	1)REFLOW SOLDERING : 240 °C 5 s MAX,				NO DEFORMATION OF CASE OF					
SOLDERING HEAT		2) SOI DI	: 220 °C MIN, FOR 10 s 2) SOLDERING IRONS : 360 °C,				EXCESSIVE LOOSENESS OF THE TERMINALS.					
		2,000	2) SOLDERING IRONS : 360 °C, FOR 5 s							×		
SOLDERABILITY			SOLDERED AT SOLDER TEMPERATURE, 240±3°C,				A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF					
		FOR IMM	FOR IMMERSION DURATION, 2 s.				JRFAC	E BEIN	IG IMMERSED.			
COUN	Т	ESCRIPTION	ON OF REVISIONS		DESIC	SNED			CHECKED		DATE	
REMARK (1) TEMPERATURE RISE INCLUDED WHEN ENERGIZED.												
			ES A LONG-TERM STORAGE STATE DUCT BEFORE THE BOARD MOUNTED.			APPROVED CHECKED DESIGNED		-	HS. OKAWA	11. C		
									HT. YAMAGUCHI			
ا اسلمت ا	:	(£;)						-	SY. KAMIGA	11. 02. 01		
	·	-	fer to MIL-STD-1344.			DRAWN		VVN	HK. SUNADORI 11. 02.		2. 01	
Note QT:Qu						RAWING NO. ELC4-083933-						
H(7			CATION SHEET	PART NO.		FX4B1-20S-1. 27SV (7				1/1		
EODM UDOO11		NOOL E	OSE ELECTRIC CO., LTD.			CODE NO.		CL574-0311-8-71				