

# NDD03N40Z, NDT03N40Z

## N-Channel Power MOSFET 400 V, 3.4 Ω

### Features

- 100% Avalanche Tested
- Extremely High dv/dt Capability
- Gate Charge Minimized
- Very Low Intrinsic Capacitance
- Improved Diode Reverse Recovery Characteristics
- Zener-protected
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

### ABSOLUTE MAXIMUM RATINGS (T<sub>J</sub> = 25°C unless otherwise noted)

Parameter	Symbol	NDD	NDT	Unit
Drain-to-Source Voltage	V <sub>DSS</sub>	400		V
Gate-to-Source Voltage	V <sub>GS</sub>	±30		V
Continuous Drain Current Steady State, T <sub>C</sub> = 25°C (Note 1)	I <sub>D</sub>	2.1	0.5	A
Continuous Drain Current Steady State, T <sub>C</sub> = 100°C (Note 1)	I <sub>D</sub>	1.3	0.3	A
Power Dissipation Steady State, T <sub>C</sub> = 25°C	P <sub>D</sub>	37	2.0	W
Pulsed Drain Current	I <sub>DM</sub>	8.0	7.2	A
Continuous Source Current (Body Diode)	I <sub>S</sub>	2.1	0.5	A
Single Pulse Drain-to-Source Avalanche Energy (I <sub>D</sub> = 1 A)	EAS	42		mJ
Peak Diode Recovery (Note 2)	dv/dt	12		V/ns
Maximum Temperature for Soldering Leads	T <sub>L</sub>	260		°C
Operating Junction and Storage Temperature	T <sub>J</sub> , T <sub>STG</sub>	-55 to +150		°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Limited by maximum junction temperature
2. I<sub>S</sub> ≤ 2.4 A, di/dt ≤ 400 A/μs, V<sub>DD</sub> ≤ BV<sub>DSS</sub>, T<sub>J</sub> = +150°C

### THERMAL RESISTANCE

Parameter	Symbol	Value	Unit
Junction-to-Case (Drain) NDD03N40Z	R <sub>θJC</sub>	3.4	°C/W
Junction-to-Ambient Steady State	R <sub>θJA</sub>		°C/W
NDD03N40Z (Note 4)		42	
NDD03N40Z-1 (Note 3)		96	
NDT03N40Z (Note 4)		62	
NDT03N40Z (Note 5)		149	


3. Insertion mounted
4. Surface mounted on FR4 board using 1" sq. pad size (Cu area = 1.127" sq. [2 oz] including traces)
5. Surface-mounted on FR4 board using minimum recommended pad size (Cu area = 0.026" sq. [2 oz]).




ON Semiconductor®

<http://onsemi.com>


V <sub>(BR)DSS</sub>	R <sub>DS(ON) MAX</sub>
400 V	3.4 Ω @ 10 V



SOT-223  
CASE 318E  
STYLE 3



DPAK  
CASE 369C  
STYLE 2



IPAK  
CASE 369D  
STYLE 2

### MARKING & ORDERING INFORMATION

See detailed ordering, marking and shipping information in the package dimensions section on page 3 of this data sheet.

# NDD03N40Z, NDT03N40Z

## ELECTRICAL CHARACTERISTICS (T<sub>J</sub> = 25°C unless otherwise noted)

Characteristic	Symbol	Test Conditions	Min	Typ	Max	Unit
----------------	--------	-----------------	-----	-----	-----	------

### OFF CHARACTERISTICS

Drain-to-Source Breakdown Voltage	V <sub>(BR)DSS</sub>	V <sub>GS</sub> = 0 V, I <sub>D</sub> = 1 mA	400			V
Drain-to-Source Breakdown Voltage Temperature Coefficient	V <sub>(BR)DSS</sub> /T <sub>J</sub>	Reference to 25°C, I <sub>D</sub> = 1 mA		450		mV/°C
Drain-to-Source Leakage Current	I <sub>DSS</sub>	V <sub>DS</sub> = 400 V, V <sub>GS</sub> = 0 V	T <sub>J</sub> = 25°C		1	μA
			T <sub>J</sub> = 125°C		50	
Gate-to-Source Leakage Current	I <sub>GSS</sub>	V <sub>GS</sub> = ±20 V			±10	μA

### ON CHARACTERISTICS (Note 6)

Gate Threshold Voltage	V <sub>GS(TH)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 50 μA	3.0	3.9	4.5	V
Negative Threshold Temperature Coefficient	V <sub>GS(TH)</sub> /T <sub>J</sub>	Reference to 25°C, I <sub>D</sub> = 50 μA		9.8		mV/°C
Static Drain-to-Source On Resistance	R <sub>DS(on)</sub>	V <sub>GS</sub> = 10 V, I <sub>D</sub> = 0.6 A		3.0	3.4	Ω
Forward Transconductance	g <sub>FS</sub>	V <sub>DS</sub> = 15 V, I <sub>D</sub> = 0.6 A		1.2		S

### DYNAMIC CHARACTERISTICS

Input Capacitance (Note 7)	C <sub>iss</sub>	V <sub>DS</sub> = 50 V, V <sub>GS</sub> = 0 V, f = 1 MHz		140		pF
Output Capacitance (Note 7)	C <sub>oss</sub>			17		
Reverse Transfer Capacitance (Note 7)	C <sub>rss</sub>			3.0		
Effective output capacitance, energy related (Note 9)	C <sub>o(er)</sub>	V <sub>GS</sub> = 0 V, V <sub>DS</sub> = 0 to 320 V		10		
Effective output capacitance, time related (Note 10)	C <sub>o(tr)</sub>	I <sub>D</sub> = constant, V <sub>GS</sub> = 0 V, V <sub>DS</sub> = 0 to 320 V		20		
Total Gate Charge (Note 7)	Q <sub>g</sub>	V <sub>DS</sub> = 200 V, I <sub>D</sub> = 2.4 A, V <sub>GS</sub> = 10 V		6.6		nC
Gate-to-Source Charge (Note 7)	Q <sub>gs</sub>			1.7		
Gate-to-Drain ("Miller") Charge (Note 7)	Q <sub>gd</sub>			3.5		
Plateau Voltage	V <sub>GP</sub>			6.9		
Gate Resistance	R <sub>g</sub>			9.0		Ω

### RESISTIVE SWITCHING CHARACTERISTICS (Note 8)

Turn-on Delay Time	t <sub>d(on)</sub>	V <sub>DD</sub> = 200 V, I <sub>D</sub> = 2.4 A, V <sub>GS</sub> = 10 V, R <sub>G</sub> = 0 Ω		10		ns
Rise Time	t <sub>r</sub>			7.0		
Turn-off Delay Time	t <sub>d(off)</sub>			13		
Fall Time	t <sub>f</sub>			5.0		

### SOURCE-DRAIN DIODE CHARACTERISTICS

Diode Forward Voltage	V <sub>SD</sub>	I <sub>S</sub> = 0.5 A, V <sub>GS</sub> = 0 V	T <sub>J</sub> = 25°C		0.8	1.5	V
			T <sub>J</sub> = 100°C		0.7		
Reverse Recovery Time	t <sub>rr</sub>	V <sub>GS</sub> = 0 V, V <sub>DD</sub> = 30 V, I <sub>S</sub> = 2.4 A, d <sub>i</sub> /d <sub>t</sub> = 100 A/μs		152		ns	
Charge Time	t <sub>a</sub>			62			
Discharge Time	t <sub>b</sub>			90			
Reverse Recovery Charge	Q <sub>rr</sub>			452			nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

6. Pulse Width ≤ 380 μs, Duty Cycle ≤ 2%.

7. Guaranteed by design.




8. Switching characteristics are independent of operating junction temperatures.

9. C<sub>o(er)</sub> is a fixed capacitance that gives the same stored energy as C<sub>oss</sub> while V<sub>DS</sub> is rising from 0 to 80% V<sub>(BR)DSS</sub>

10. C<sub>o(tr)</sub> is a fixed capacitance that gives the same charging time as C<sub>oss</sub> while V<sub>DS</sub> is rising from 0 to 80% V<sub>(BR)DSS</sub>

# NDD03N40Z, NDT03N40Z

## MARKING DIAGRAMS



A = Assembly Location  
 Y = Year  
 W, WW = Work Week  
 3N40Z = Specific Device Code  
 G or ■ = Pb-Free Package  
 (\*Note: Microdot may be in either location)

## ORDERING INFORMATION

Device	Package	Shipping†
NDD03N40Z-1G	IPAK (Pb-Free, Halogen Free)	75 Units / Rail
NDD03N40ZT4G	DPAK (Pb-Free, Halogen Free)	2500 / Tape & Reel
NDT03N40ZT1G	SOT-223 (Pb-Free, Halogen Free)	1000 / Tape & Reel
NDT03N40ZT3G	SOT-223 (Pb-Free, Halogen Free)	4000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# NDD03N40Z, NDT03N40Z

## TYPICAL CHARACTERISTICS




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Gate-to-Source Voltage




Figure 4. On-Resistance vs. Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature






Figure 6. Breakdown Voltage Variation with Temperature

# NDD03N40Z, NDT03N40Z


## TYPICAL CHARACTERISTICS




**Figure 7. Threshold Voltage Variation with Temperature**




**Figure 8. Drain-to-Source Leakage Current vs. Voltage**




**Figure 9. Capacitance Variation**



**Figure 10. Gate-to-Source and Drain-to-Source Voltage vs. Total Charge**




**Figure 11. Resistive Switching Time Variation vs. Gate Resistance**




**Figure 12. Diode Forward Voltage vs. Current**

# NDD03N40Z, NDT03N40Z


## TYPICAL CHARACTERISTICS




**Figure 13. Maximum Rated Forward Biased Safe Operating Area for NDT03N40Z**



**Figure 14. Maximum Rated Forward Biased Safe Operating Area for NDD03N40Z**



**Figure 15. Thermal Impedance (Junction-to-Ambient) for NDT03N40Z**





**Figure 16. Thermal Impedance (Junction-to-Case) for NDD03N40Z**

# NDD03N40Z, NDT03N40Z

## PACKAGE DIMENSIONS

SOT-223 (TO-261)  
CASE 318E-04  
ISSUE N




NOTES:  
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.  
2. CONTROLLING DIMENSION: INCH.

DIM	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	1.50	1.63	1.75	0.060	0.064	0.068
A1	0.02	0.06	0.10	0.001	0.002	0.004
b	0.60	0.75	0.89	0.024	0.030	0.035
b1	2.90	3.06	3.20	0.115	0.121	0.126
c	0.24	0.29	0.35	0.009	0.012	0.014
D	6.30	6.50	6.70	0.249	0.256	0.263
E	3.30	3.50	3.70	0.130	0.138	0.145
e	2.20	2.30	2.40	0.087	0.091	0.094
e1	0.85	0.94	1.05	0.033	0.037	0.041
L	0.20	---	---	0.008	---	---
L1	1.50	1.75	2.00	0.060	0.069	0.078
HE	6.70	7.00	7.30	0.264	0.276	0.287
θ	0°	—	10°	0°	—	10°

STYLE 3:  
PIN 1. GATE  
2. DRAIN  
3. SOURCE  
4. DRAIN


### SOLDERING FOOTPRINT



# NDD03N40Z, NDT03N40Z

## PACKAGE DIMENSIONS

### DPAK (SINGLE GAUGE) CASE 369C ISSUE E



**NOTES:**


1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: INCHES.
3. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS b3, L3 and Z.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.006 INCHES PER SIDE.
5. DIMENSIONS D AND E ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
6. DATUMS A AND B ARE DETERMINED AT DATUM PLANE H.
7. OPTIONAL MOLD FEATURE.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.086	0.094	2.18	2.38
A1	0.000	0.005	0.00	0.13
b	0.025	0.035	0.63	0.89
b2	0.028	0.045	0.72	1.14
b3	0.180	0.215	4.57	5.46
c	0.018	0.024	0.46	0.61
c2	0.018	0.024	0.46	0.61
D	0.235	0.245	5.97	6.22
E	0.250	0.265	6.35	6.73
e	0.090 BSC		2.29 BSC	
H	0.370	0.410	9.40	10.41
L	0.055	0.070	1.40	1.78
L1	0.114 REF		2.90 REF	
L2	0.020 BSC		0.51 BSC	
L3	0.035	0.050	0.89	1.27
L4	---	0.040	---	1.01
Z	0.155	---	3.93	---

**STYLE 2:**

- PIN 1. GATE
- DRAIN
- SOURCE
- DRAIN

### SOLDERING FOOTPRINT\*



SCALE 3:1  $\left( \frac{\text{mm}}{\text{inches}} \right)$


\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.



# NDD03N40Z, NDT03N40Z

## PACKAGE DIMENSIONS

### IPAK CASE 369D ISSUE C



- NOTES:  
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.  
2. CONTROLLING DIMENSION: INCH.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.235	0.245	5.97	6.35
B	0.250	0.265	6.35	6.73
C	0.086	0.094	2.19	2.38
D	0.027	0.035	0.69	0.88
E	0.018	0.023	0.46	0.58
F	0.037	0.045	0.94	1.14
G	0.090 BSC		2.29 BSC	
H	0.034	0.040	0.87	1.01
J	0.018	0.023	0.46	0.58
K	0.350	0.380	8.89	9.65
R	0.180	0.215	4.45	5.45
S	0.025	0.040	0.63	1.01
V	0.035	0.050	0.89	1.27
Z	0.155	---	3.93	---

- STYLE 2:  
PIN 1. GATE  
2. DRAIN  
3. SOURCE  
4. DRAIN

**ON Semiconductor** and **ON** are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>  
For additional information, please contact your local Sales Representative