



# ATP Embedded Modules SlimSATA

Targeted Product Portfolio, Engineered Specifically for Your Mission Critical Applications



With its small size and JEDEC standard, the ATP SlimSATA with PowerProtector is an ideal solution for business critical embedded and networking applications. Featuring a standard SATA interface and premium grade NAND flash components, ATP SlimSATA offers ultra-fast read performance of up to 530 MB/s and write performance of up to 440 MB/s. The ATP SlimSATA offers an alternative solution for embedded applications such as IPC, blades, AdvancedTCA, single board computers, surveillance & security and networking , which have space constraints and requires high performance and reliability.

## Key Features

- JEDEC standard: MO-297 (Slim SATA) compliant
- Enhanced endurance with Advanced Wear Leveling algorithm
- Built-in hardware-based data protection technology during power failure - PowerProtector
- Supports S.M.A.R.T. ATA feature set
- RoHS compliant and CE/FCC certification

## Applications

- IPC
- Blades
- AdvancedTCA
- Single board computers
- Surveillance & security
- Networking appliance





## Specifications

Product Name	SlimSATA		
Flash Type	SLC	iTemp MLC	MLC
Density	8GB to 128GB	16GB to 512GB	16GB to 512GB
Performance	Sequential Read up to 530 MB/s	Sequential Read up to 530MB/s	Sequential Read up to 530MB/s
	Sequential Write up to 430 MB/s	Sequential Write up to 440MB/s	Sequential Write up to 440MB/s
	Random Read IOPS up to 76,520	Random Read IOPS up to 72,040	Random Read IOPS up to 72,040
Interface	SATA III 6 Gb/s		
Operating Temperature	-40°C to +85°C	-40°C to +85°C	0°C to 70°C
Reliability	Advanced Wear Leveling, AutoRefresh, PowerProtector		
	TBW* (max.) : 5,120 TB	TBW* (max.) : 1,066.68 TB	TBW* (max.) : 1,280 TB
	MTBF @ 25°C: >5,000,000 hours	MTBF @ 25°C: >2,000,000 hours	MTBF @ 25°C: >2,000,000 hours
Dimensions: LxWxH (mm)	54.0 x 39.0 x 4.0		

\* All TBW data listed are under highest sequential write value in each product line. The TBW data are subject to change by density, configuration and customers' applications.

## Ordering Information

Density	SlimSATA		
	SLC	iTemp MLC	MLC
8GB	AF8GSSEL-VADXP	-	-
16GB	AF16GSSEL-VADXP	AF16GSMEL-VAEIP	AF16GSMEL-VAEXP
32GB	AF32GSSEL-VADXP	AF32GSMEL-VAEIP	AF32GSMEL-VAEXP
64GB	AF64GSSEL-VABXP	AF64GSMEL-VADIP	AF64GSMEL-VADXP
128GB	AF128GSSEL-VAAXP	AF128GSMEL-VACIP	AF128GSMEL-VACXP
256GB	-	AF256GSMEL-VABIP	AF256GSMEL-VABXP
512GB	-	AF512GSMEL-VABIP	AF512GSMEL-VABXP

### ATP TAIWAN(HQ)

TEL: +886-2-2659-6368  
FAX: +886-2-2659-4982  
sales-apac@atpinc.com

### ATP USA

TEL: +1-408-732-5000  
FAX: +1-408-732-5055  
sales@atpinc.com

### ATP EUROPE

TEL: +49-89-374-9999-0  
FAX: +49-89-374-9999-29  
sales-europe@atpinc.com

### ATP JAPAN

TEL: +81-3-6206-8097  
FAX: +81-3-6206-8098  
sales-japan@atpinc.com

### ATP CHINA

TEL: +86-21-5080-2220  
FAX: +86-21-9687-0000-026  
sales@cn.atpinc.com