



**NOTES:**

- A. Material:
- 1. Housing: PA66 UL 94V-0 Color: Black
- 2. Terminal: COPPER ALLOY, TIN PLATED
- B Electrical Characteristics:
- 1. Rating: 15A 250V ~ UL, CUL
- 10A 250V ~ VDE, SEMKO, CCC
- 2. Electric Strength: AC 2,000 V FOR ONE MINUTE
- 3. Insulation Resistance: 100MΩ MIN. AT 500V DC
- C. Approvals:
- UL, CUL, VDE, SEMKO, CCC

**RoHS compliant**

|           |      |   |                 |  |            |          |            |          |  |
|-----------|------|---|-----------------|--|------------|----------|------------|----------|--|
| Scale     | 1:1  |   |                 |  |            |          |            |          |  |
| TOLERANCE |      |   |                 |  |            |          |            |          |  |
| X.X       | ±0.3 |   |                 |  |            | Drawn    | 14.12.2007 | N.Schulz |  |
| X.XX      | ±0.2 |   |                 |  |            | Approved | 12.12.2012 | Winnie   |  |
| X.XXX     | ±0.1 | ③ | Change of plant |  | 18.12.2012 |          |            | Winnie   |  |
| DIM       | TOL  | ② | Update          |  | 08.07.2009 |          |            | Dean     |  |
| Ang.      | ±3°  | ① | Drawn           |  | 14.12.2007 |          |            | N.Schulz |  |
| UNIT      | mm   |   | Modification    |  |            |          |            |          |  |



|                 |              |
|-----------------|--------------|
| Customer-No.    |              |
| ASSMANN WSW-No. | A-KGS-S/A    |
| Drawing-No.     | ASS 0889B CO |
| Replace         | rev03        |
|                 | SHEET        |

|     |   |   |   |   |   |   |
|-----|---|---|---|---|---|---|
| 1   | 2 | 3 | 4 | 5 | 6 | 7 |
| A   | B | C | D | E | F | G |
| H   | G | F | E | D | C | B |
| 1   | 2 | 3 | 4 | 5 | 6 | 7 |
| H   | G | F | E | D | C | B |
| 187 |   |   |   |   |   |   |