



Pos.	A	B	C	D	E	ØF	G <sup>+0.2</sup>	H	Part NO. Bulk package	Part NO. Single package
9	31.7	25.0	30.0	32.7	15.0	5.0	9.0	9.0	165X17459X	165X17459XE
15	40.0	33.3	32.0	34.7	15.0	5.0	9.0	9.0	165X17469X	165X17469XE
25	53.7	47.0	35.0	37.7	15.0	7.0	12.2	10.0	165X17479X	165X17479XE
37	70.2	63.5	41.0	43.7	15.0	7.0	13.5	11.0	165X17489X	165X17489XE
50	67.8	61.1	41.0	43.7	17.7	9.3	15.3	12.7	165X17499X	165X17499XE

Directive 2002/95/EC  
"RoHS"  
Compliant

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

CUSTOMER APPROVAL DATE:

NAME: TITLE:

COMPANY NAME:

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

- NOTES:**
1. CASE: ZINC DIE CAST; NICKEL PLATED
  2. SHORT SCREW: STEEL; NICKEL PLATED
  3. CABLE BUSHING: TPE
  4. CABLE STRAIN RELIEF: STEEL; NICKEL PLATED
  5. ATTENUATION FACTOR >60dB BETWEEN 300 MHz AND 900 MHz

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.  
OWNERSHIP AND COPYRIGHT OF CONEC GmbH  
DO NOT ALTER CAD DRAWING BY HAND

tolerance		dim. in mm	
2007	date	name	
drawn	17.07.	Lehmenkühler	
appd.	17.07.	Kühle	
norm			
d-old			
a	Origin		
rev.	description	date	name



scale:	1:1
material:	SEE NOTES
title:	<b>METAL HOOD</b> 9-50pos. EMI / RFI SHIELDING with straight cable exit and short screws M3
dwg no:	AutoCAD 2006
	DIN-A 4
	sh: 1/1
part no:	SEE TABLE