



GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:
SEE GS-12-447

- NOTE-1: COMPATIBLE WITH NARROW AND WIDE BODY
- NOTE-2: PCB FINISH HOLE DIAMETER
SEE GS-12-447
- NOTE-3: IF SUFFIX "P" IS ADDED IN P/N, PACKAGING IS IN TRAYS,
BUT CONNECTOR MARKING IS WITHOUT "P"
Example : HM1FxxxxxxxxH6PLF, marking: HM1FxxxxxxxxH6LF

European Views

TIN LEAD PART NUMBER

Part Number: HM1S4xFER000H6	
PIN COUNT	024 WAYS-REPLACE x BY 1 096 WAYS-REPLACE x BY 3
RANGE	048 WAYS-REPLACE x BY 2 192 WAYS-REPLACE x BY 4

LEAD-FREE PART NUMBER

Part Number: HM1S4xFER000H6LF	
PIN COUNT	024 WAYS-REPLACE x BY 1 096 WAYS-REPLACE x BY 3
RANGE	048 WAYS-REPLACE x BY 2 192 WAYS-REPLACE x BY 4

rev	ecn no	dr	date
F	-	CHA	1999/10/05
G	LS05-004	MLE	2005/02/17
H	LS06-0095	LGO	2006/07/03
J	LS06-0159	MLE	2006/10/23
K	LS07-0266	MLE	2007/11/06
-	-	-	-
-	-	-	-

www.fciconnect.com		surface ISO 1302 ✓	tolerance std ISO 406 ISO 1101	projection ⊕	mm
TOLERANCES UNLESS OTHERWISE SPECIFIED					
Dr	CHAMPION	1992/10/07	ANGULAR	0.X ±0.1	size Scale
Eng	LENOIR	1992/10/07	LINEAR	0.XX ±0.1	A3 3
Chr	LEGARE	1992/10/07	0.XX' ±2'	0.XXX ±0.1	ECN LS07-0266
Appr	LEGARE	1992/10/07	Product family	METRAL	Spec ref -
FCj		title METRAL FEM. 4 ROW STRAIGHT PRESS		Part C-8626-0082	
		PCB THICKNESS: 2.4 mm MINIMUM		Rev. K	
catalog no		-		CUSTOMER sheet 1 of 1	

REV F - 2006-04-17