



| SWITCH FUNCTION | |
|-----------------|--------|
| POS. 1 | POS. 2 |
| ON | OFF |
| 2-1 | OPEN |

NOTES:

- ALL DIMENSIONS IN MM [INCH]
- GENERAL TOLERANCE: 0.0=±0.4
0.00=±0.25
- TERM. NOS. FOR REF. ONLY
- RATING: 16A, 125VAC, 10A, 250VAC UL&CUL APPROVED
10A 125VAC, 6A 250V AC VDE APPROVED
- CONTACT RESISTANCE: 50m ohm max.
- INSULATION RESISTANCE: DC 500V 100M ohm min.
- DIELECTRIC STRENGTHS: AC 1500V 1 minute
- OPERATING TEMP.: 0°C to 85°C
- 3V RED LED
- ▲ DENOTES CRITICAL PARAMETER.

E-SWITCH®

| | | | | |
|------|---------|-------------------------|---------|------|
| B | 13813 | UPDATE PART AND NOTES | 3/2/04 | AR |
| A | 13317 | RELEASED FOR PRODUCTION | 7/25/03 | AR |
| REV. | ECN No. | DESCRIPTION | DATE | CHKD |

| | | | | |
|---------------------|---------|----|---------|-----|
| TITLE | | | | |
| RR3112LBLKBLKREDEF3 | | | | |
| SCALE | DATE | DR | DWG | REV |
| 2:1 | 7/25/03 | AR | F130452 | B |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED