



LVSM1NP

LVSM1PL

Project Name \_\_\_\_\_

Catalog No. \_\_\_\_\_ Date \_\_\_\_\_

Our Low Voltage Wall Switches are designed for virtually any area. The soft contours of its architecturally-pleasing design fit easily into any décor. Momentary version switches are available and feature multiple button configurations making them the perfect switch solution for low voltage occupancy sensors, daylighting controls and networked lighting control panels.

**Product Features**

- Attractive, architecturally pleasing design
- Momentary or latching button action
- 1-4 buttons with or without LED
- Mounts to standard single-gang box
- California Title 24 compliant
- Five-year limited warranty
- Low voltage device: 24VDC

**Compliance and Certification**



**Ordering Information**

LVS	—	[ ]	—	[ ]	—	[ ]	—	[ ]
<b>SWITCH MODEL</b>		<b>SWITCH TYPE</b>		<b>NUMBER OF BUTTONS</b>		<b>PILOT</b>		<b>COLOR</b>
LVS		M Momentary L Latching		1-4		PL w/ Pilot LEDs NP No Pilot		WH White IV Ivory LA Light Almond G Gray

Latching buttons are for special applications only, consult factory if you are not certain about how to use a latching button

## General Specifications

Electrical Ratings	Each switch: 100mA @ 30VDC Max Each pilot LED: 18-30VDC, internal 2.2kohm, ½ Watt resistor
Configurations	1 - 4 buttons, with or without pilot LED Momentary
Operating environment	Indoor use only Operating temperature: 32° to 122°F (0° to 50°C) Relative humidity (non-condensing): 10%-90%
Construction	Housing – Rugged, high-impact, injection-molded plastic Color-coded leads
Dimensions	1.88"W x 4.25"H x 1.56"D (47.75mm x 107.95mm x 39.63mm)
Weight	3.0 oz [85.0 g]
Color	White, Ivory, Light Almond, Gray
Mounting	Single-gang NEMA-style switch box (average switch box) Decorator-style wall plate not included
Warranty	Five-year limited