9080 Smart Trend Meter Analyzes, Interprets and TRENDS readings...

(BDU) Total (g) VA

9080 Data Sheet 0613

Ani 9080

0.473 ISO

Smart Trend Meter

 \bigcirc \triangleright

0.4

BENEFITS

- Find machine faults before they stop your machine
- Increase productivity and lower maintenance costs

FEATURES

- Collect data
- Trend data using VibTrend software
- Standard Cable mounted accelerometer with magnet
- Built-in Bluetooth communication capability
- USB docking station to download to a PC
- ISO built-in Alarms
 Easily identify bearing problems with BDU Reading
- Easily identify problems with built-in band filters:
 1X (unbalance)
 2X (misalignment)
 3X (looseness)
- 800 line FFT (spectrum)
- Listen to bearing noise with optional Bluetooth headphones
- Ruggedized IP67 case
 3-year Limited Warranty

PUT THE TPI 9080 TO WORK:

- Commercial & Industrial HVAC Food Processing Manufacturing Mining Packaging Petrochemical Pulp and Paper
- Power Plants
- Utilities
- Automoti
- Automotive

New VibTrend

Identify the vibration problem: unbalance, misalignment or looseness; in addition to the bearing condition

VibTrend Standard Software

Optional A9082 Combo: Stroboscope, Tachometer and Flashlight



- **1. Stroboscope:** freezes moving parts.
- 2. Tachometer: flash rate is automatically stored as the run speed.
- **3. Flashlight:** hold the strobe button down for 2-seconds turns the light on.

www.testproductsintl.com

9080 Smart Trend Meter

The TPI 9080 is a simple, easy to use, low cost vibration meter that records, analyzes and displays vibration signals at the push of a button.

VibTrend standard software gives you greater ease of use and flexibility. Windows 7[™] compatible

- Store analyze and report on all your vibration parameters in one place; up to 10 assets with 10 readings per asset standard; unlimited assets with 10 readings per asset with optional A9084 VibTrend Pro software.
- All information is just a click away. Color coded alarms highlight problems. Trend lines show problems before they happen.

Overall machine and bearing conditions: vibration values are displayed with color coded alarm levels for

ISO values and Bearing Damage (BDU).



800 Line 1450 RPM 0.14 in/s

Identify complex issues: 800-line spectrum with zoom and cursor.

- Size: H 7.95" W 2.36"
- Weight: 9.8oz (280g)
- Environmental:
 - o Water: IP67 Waterproof
 - o Operating: 32°F to 122°F (0C to 50C)
 - o Storage: -4°F to 158°F (-20C to 70C)
- Power supply: 2xAA batteries
- Battery life: 2-years standby, 1,500 measurements or approximately 50 hours of normal use
- Frequency ranges: ISO: 2/10Hz 1kHz

g: 2Hz - 10kHz

- Frequency resolution: 100 / 800 lines
- · Displayed amplitude units: Acceleration in g / velocity in inches per second or mm per second / Bearing damage in BDU
- Displayed frequency units: Hz, CPM or RPM
- Input range: +/- 60 g
- Dynamic range: 96 dB
- Auto set up of VA bands
- Accelerometer connection: BNC connector cable with removable magnet (1mV/g - 10,000mV/g)
- Communication: Bluetooth or USB docking station and cable to PC; data integration using VibTrend software
- Reading storage: 10 assets/10 readings per asset standard; unlimited assets/10 readings per asset with optional A9084 VibTrend Pro software
- Standard accessories: A9012 IEPE accelerometer with cable and A9073 magnet, A9081 docking station with USB cable, A9083 VibTrend Standard software and carrying case.
- Optional accessories: A9082 Strobe/Flashlight, A9084 VibTrend software Pro version. A9080 Bluetooth headset, A9072 4-inch stinger and A9086 Protective boot with magnets

Industry approved ear defenders with built-in Bluetooth headphones are also available to let you listen to the bearing noise - or even listen to your phone!

