

## RJ45 bending protection sleeve - VS-08-KS/GN - 1689226

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



RJ45 bend protection sleeve, for pin insert VS-08-ST-RJ45, cable cross section up to 6 mm, color: green



### Ethernet

#### Key commercial data

Packing unit	1 1
Minimum order quantity	5 1
Weight per Piece (excluding packing)	6.33 GRM
Custom tariff number	39269097
Country of origin	United States

#### Technical data

##### Mechanical characteristics

External cable diameter	6 mm
Color	green

##### Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Degree of protection	IP20

##### Material data

Inflammability class according to UL 94	V0
Housing material	PA

#### Classifications

##### eCl@ss

eCl@ss 4.0	27141210
eCl@ss 4.1	27141210

# RJ45 bending protection sleeve - VS-08-KS/GN - 1689226

## Classifications

### eCl@ss

eCl@ss 5.0	27149110
eCl@ss 5.1	27149110
eCl@ss 6.0	27149110
eCl@ss 7.0	27149110
eCl@ss 8.0	27149110

### ETIM

ETIM 2.0	EC000241
ETIM 3.0	EC002040
ETIM 4.0	EC002040
ETIM 5.0	EC002040

### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

## Accessories

### Accessories

#### Male insert

RJ45 male insert - VS-08-ST-RJ45 - 1688573



RJ45 pin insert, CAT5e, 8-pos., shielded, IDC connection method, for litz wires AWG 26 and solid wires AWG 26 ... 24

## Drawings

Dimensioned drawing

RJ45 bending protection sleeve

