

5

4

3

2

1

受控 CONTROLLED DOCUMENT

编号 P/N	40-97XXM	版本 Rev	02	日期 Rel'd Date	Jul11,11
-----------	----------	-----------	----	------------------	----------

Description: 97 Series Solder Style Panel & Cable Mount D-Sub

Connectors

Part No: 40-97xxM

Application: For Cable

Crimp Tool: N/A

Impedance: N/A

Frequency Range: 0-15 MHz

Material: Housing Steel Nickel plated

Insulator PBT+Fiber-glass UL94-V0 White

Contact Cu-alloy, Gold plated

RoHS Compliance: Yes

Technical Detail: N/A




DRAWING NO.

40-97XXM

REVISIONS

01		OFFICIAL RELEASE			
02-20-09	T W	B Y	T		
02		CHANGE SHELL PLATING FROM YELLOW ZINC TO NICKEL; CHANGE DIMENSIONS: 3.50MAX TO 3.8REF; D DIMENSION FOR 40-9725M FROM 41.28 TO 41.10; ADD DIMENSIONS: 1.25MAX; 5.6MAX;			
03-25-11	J J	J J	D		ECO-11-0055

P/N	Pins	A	B	C	D
40-9709M	9	30.80	24.99	16.92	19.20
40-9715M	15	39.15	33.32	25.25	27.70
40-9725M	25	53.00	47.04	38.96	41.10
40-9737M	37	69.30	63.50	55.42	57.30



CUSTOMER COPY

TOLERANCE UNLESS OTHERWISE SPECIFIED		DRAWN BY	DATE
DECIMALS	mm	JEAN.JIN	03-25-11
X	± 0.5	CHECKED BY	DATE
X.X	± 0.3	JEAN.JIN	03-25-11
X.XX	± 0.1	APPROVED BY	DATE
ANGLES	± 0.5°	DONALD	03-25-11
		U/M	mm

THIS DRAWING WAS PRODUCED BY COMPUTER, DO NOT SCALE DRAWING OR UPDATE MANUALLY.

SHEET
1 OF 1DRAWING NO.
40-97XXM-CUSTSIZE
A

5

4

3

2

1