



- .035 DIA HOLE IS RECOMMENDED FOR .125 MAX THICK P.C. BOARD.
 - CONNECTOR MATES WITH ANY AMP 78 POSN PLUG.
 - POST TIPS WILL FALL WITHIN $\nabla \nabla .020$ TRUE POSITION OF EACH OTHER.
- $\nabla 4$ UL/CSA DESIGNATION STAMPED IN THIS AREA, OPTIONAL.
 $\nabla 5$ FINISH: CADMIUM PER QQ-416.
 $\nabla 6$ FINISH: ZINC PLATED PER ASTM-B-633 .000200-.000400 THK WITH SUPPLEMENTARY CHROMATE (Cr3+).

REMARKS	- $\nabla 6$.375 MAX	.275±.025	5-211596-1
	NOT RELEASED FOR PRODUCTION $\nabla 5$.275 MAX	.375±.025	211596-2
	-	.375 MAX	.275±.025	211596-1
		DIM B	DIM A	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWG: C.C.THOMAS 8-11-97	Tyco Electronics Corporation	
DIMENSIONS: INCHES		CHK: H.WYNKOOP 11-24-97	Harrisburg, PA 17105-3608	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD:	NAME: AMPLIMITE 78 POSN. RCPT ASSY WITH LOADED POSTED CONTACTS SIZE 5, SERIES 90	
0 PLC ± -		PRODUCT SPEC	SIZE: A1	
1 PLC ± -		APPLICATION SPEC	CAGE CODE: 00779	
2 PLC ± -		WEIGHT	DRAWING NO: 211596	
3 PLC ± .005		CUSTOMER DRAWING	SCALE: 4:1	
4 PLC ± -			SHEET 1 OF 1	
ANGLES ± -			REV J	