

DOL-0803-G02MC

Plug connectors and cables

ACCESSORIES





Ordering information

Туре	Part no.
DOL-0803-G02MC	6025888

Other models and accessories -> www.sick.com/Plug_connectors_and_cables

Detailed technical data

Technical specifications


Accessory group	Plug connectors and cables
Accessory family	Connecting cables with female connector
Connection type head A	Female connector, M8, 3-pin, straight
Connection type head B	Open cable ends
Connection type	Flying leads
Connector material	TPU
Connector color	Black
Locking nut material	Zinc die-cast, nickel-plated
Cable	2 m, 3-wire, PUR, halogen-free
Jacket material	PUR, halogen-free
Jacket color	Black
Cable diameter	4.4 mm
Conductor cross-section	0.25 mm ²
Shielding	Unshielded
Bending radius	
Flexible use	> 10 x cable diameter
	20 // 000/0 0/10/10/00/
	> 5 x cable diameter
Stationary position	> 5 x cable diameter
Stationary position Bending cycles	> 5 x cable diameter ≥ 4,000,000
Stationary position Bending cycles Reference voltage	> 5 x cable diameter ≥ 4,000,000 ≤ 60 V
Stationary position Bending cycles Reference voltage Current loading	> 5 x cable diameter ≥ 4,000,000 ≤ 60 V 4 A
Stationary position Bending cycles Reference voltage Current loading Traversing speed	> 5 x cable diameter ≥ 4,000,000 ≤ 60 V 4 A Max. 3 m/s
Stationary position Bending cycles Reference voltage Current loading Traversing speed Travelling distance	> 5 x cable diameter ≥ 4,000,000 ≤ 60 V 4 A Max. 3 m/s 10 m
Stationary position Bending cycles Reference voltage Current loading Traversing speed Travelling distance Acceleration	> 5 x cable diameter ≥ 4,000,000 ≤ 60 V 4 A Max. 3 m/s 10 m
Stationary position Bending cycles Reference voltage Current loading Traversing speed Travelling distance Acceleration	> 5 x cable diameter ≥ 4,000,000 ≤ 60 V 4 A Max. 3 m/s 10 m ≤ 10 m/s²
Stationary position Bending cycles Reference voltage Current loading Traversing speed Travelling distance Acceleration	> 5 x cable diameter \geq 4,000,000 \leq 60 V 4 A Max. 3 m/s 10 m \leq 10 m/s ² Zones with oils and lubricants
Bending cycles Reference voltage Current loading Traversing speed Travelling distance Acceleration Application	> 5 x cable diameter \geq 4,000,000 \leq 60 V 4 A Max. 3 m/s 10 m \leq 10 m/s ² Zones with oils and lubricants
Bending cycles Reference voltage Current loading Traversing speed Travelling distance Acceleration Application	> 5 x cable diameter ≥ 4,000,000 ≤ 60 V 4 A Max. 3 m/s 10 m ≤ 10 m/s² Zones with oils and lubricants Drag chain operation
Bending cycles Reference voltage Current loading Traversing speed Travelling distance Acceleration Application Authorizations	> 5 x cable diameter ≥ 4,000,000 ≤ 60 V 4 A Max. 3 m/s 10 m ≤ 10 m/s² Zones with oils and lubricants Drag chain operation UL

Ambient operating temperature	
Flexible use	-25 °C +80 °C
Stationary position	-40 °C +80 °C
Head	-25 °C +90 °C

Classifications

ECI@ss 5.0	19030312
ECI@ss 5.1.4	19030312
ECI@ss 6.0	27060304
ECI@ss 6.2	27060304
ECI@ss 7.0	27060304
ECI@ss 8.0	27060304
ECI@ss 8.1	27060304
ECI@ss 9.0	27060304
ETIM 5.0	EC000830
ETIM 6.0	EC000830
UNSPSC 16.0901	26121604

Dimensional drawing (Dimensions in mm (inch))



SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

