



A ROW		X	Y	△6 △4	3-917657-5
B ROW		X	Y	△6 △3	3-917657-3
				△6 △2	3-917657-2
A ROW		Y	Y	△6 △4	2-917657-5
B ROW		Y	Y	△6 △3	2-917657-3
				△6 △2	2-917657-2
A ROW		X	X	△6 △4	1-917657-5
B ROW		X	X	△6 △3	1-917657-3
				△6 △2	1-917657-2

KEYING LOCATION		A ROW KEYING	B ROW KEYING	FINISH	製品番号	PART NO.
					<b>TE</b> TE Connectivity	
WIRE RANGE	INSULATION DIA	NAME				
mm (AWG - )	mm φ	ダイナミック D-3200 垂直タイプ 10極 ヘッダーアセンブリー				
MATERIAL	FINISH	DYNAMIC D-3200 10 POS.V-HDR ASS'Y				
SEE NOTE 注記参照	SEE NOTE 注記参照	一般公差 (GENERAL TOLERANCE)				
DR. 24/APR/'95	DE. 24/APR/'95	10MF ±0.3	SIZE A3	LOC J	NUMBER C-917657	
CHK. 24/APR/'95	APP. 24/APR/'95	100MF ±0.4	SCALE 2-1	REV. B1	SHEET 1 OF 1	
		300MF ±0.45				
		角 度 ±3'				

B1	REVISED PER ECO-11-005030	RK	HMR	25MAR11
LTR	REVISION RECORD	DR	CHK	DATE