



MAXIMUM PANEL THICKNESS: 2.66 mm
RECOMMENDED MOUNTING TORQUE: 4.5 INCH LBS MAX.

CONSTRUCTION:
 CONNECTOR BODY-----BRASS
 DIELECTRIC-----PLOY-BUTYLENE TEREPHTHALATE (WHITE COLOR)
 CENTER CONTACT-----PHOSPHOR BRONZE
 LOCK WASHER-----PHOSPHOR BRONZE
 NUT-----BRASS

FINISH:
 CONNECTOR BODY-----NICKEL PLATING
 CENTER CONTACT-----GOLD PLATING (10µ")
 LOCK WASHER-----NICKEL PLATING
 NUT-----NICKEL PLATING

MECHANICAL & ELECTRIC CHARACTERISTICS:
 PER PRODUCT SPECIFICATION PS-73598-0019

MATERIAL & FINISH:
 PER PRODUCT SPECIFICATION PS-73598-0019

PACKAGING: INDIVIDUAL PACKAGING WITH PLASTIC BAGS

P/N: 73115-5003 BULK PACK
 P/N: 73171-3130 IS SINGLE ASSEMBLY 73115-5003 IN BAG WITH LABEL

CHG: ADDED BAGGING OPTION. EC NO: URF2007-0455 DRAWN: ARROBERTSON 2007/05/14 CHKD: 2007/05/14 APPR: JIM ENEER 2007/05/14 REVISIONS H1	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION																
		<table border="1"> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> <tr> <td>4 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>3 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>2 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>1 PLACE</td> <td>± ---</td> <td>± ---</td> </tr> </table>			mm	INCH	4 PLACES	± ---	± ---	3 PLACES	± ---	± ---	2 PLACES	± ---	± ---	1 PLACE	± ---	± ---	DRAWN BY DATE IRIS WANG 1990/12/28		TITLE 50 OHM BNC JACK STR			
			mm	INCH																				
		4 PLACES	± ---	± ---																				
3 PLACES	± ---	± ---																						
2 PLACES	± ---	± ---																						
1 PLACE	± ---	± ---																						
ANGULAR ±1/2°		CHECKED BY DATE 1990/12/28		APPROVED BY DATE 1990/12/28																				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SEE TABLE		DOCUMENT NO. SD-73115-5003		SHEET NO. 1 OF 1																		



THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION