

Park position - EV-T2AC-PARK - 1624148

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Retainer for Vehicle Connector as parking position at charging stations (EVSE), Type 2, IEC 62196-2, Front mounting

Product Description

Retainer for Vehicle Connector as parking position at charging stations for E-Mobility (EVSE)

Why buy this product

☑ Certified in accordance with IATF 16949:2016 and ISO 9001:2015



Key Commercial Data

Packing unit	1 STK
GTIN	4 055626 242828
GTIN	4055626242828

Technical data

Product definition

Product type	Retainer for Vehicle Connector as parking position at charging stations (EVSE)
Standards/regulations	IEC 62196-2
Charging standard	Туре 2
Charging mode	Mode 3

Dimensions

Height	75 mm
Width	75 mm
Depth	44.7 mm
Bore dimensions	60 mm x 60 mm

Ambient conditions

Ambient temperature (operation)	-30 °C 50 °C
Ambient temperature (storage/transport)	-40 °C 80 °C



Park position - EV-T2AC-PARK - 1624148

Technical data

Ambient conditions

Degree of protection	IP54	
Mechanical properties		
Vehicle Connector fixing	With locking clips for locking contour	
Removal of the Vehicle Connector	Lifting and removal	
Detection of the Vehicle Connector	On request	
Mounting		
Possible mounting positions	Front mounting	
Restrictions to mounting position	Only 0 to 45 degree frontal inclination possible, see figure	
Mounting hole diameter	6.00 mm (ø)	
Design		
Housing color	black	
Customer variations	On request	
Material		
Material	Plastic	
Flammability rating	V0	
Environmental Product Compliance		
China RoHS	Environmentally friendly use period: unlimited = EFUP-e	

Drawings

Schematic diagram



The attached AC Vehicle Connector is raised in the holder, releasing it from the integrated locking clip, and it can then be removed. Dimensional drawing

No hazardous substances above threshold values



Dimensional drawing



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com