



- NOTE**
1. SMT LEAD-COPLANARITY: 0.1 MAX.
 2. THIS PRODUCT HAS NO POLARITY TO PATTERN FOR MOUNTING.
 3. STACKING HEIGHT FROM LEAD TO LEAD. (REFERENCE DIMENSIONS)
 4. BOARD DISTANCE
 5. EMBOSS CARRIER TAPE PACKAGE IS APPLIED ON THIS PRODUCT. PLEASE REFER TO THE SHEET 2/2 FOR THE RETAILS.

2	PHOSPHOR BRONZE	CONTACT: GOLD PLATING 0.76µm MIN LEAD : GOLD PLATING 0.03µm MIN UNDER : NICKEL PLATING 1.3µm MIN	3	PHOSPHOR BRONZE	LEAD : GOLD PLATING 0.03µm MIN UNDER : NICKEL PLATING 1.3µm MIN
1	LCP	BEIGE, UL94V-0			
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 4:1	COUNT	DESCRIPTION OF REVISIONS	
DESIGNED		CHECKED		DATE	
APPROVED : NH. NAKATA		16.11.10		DRAWING NO. EDC-151991-93-00	
CHECKED : HT. YAMAGUCHI		16.11.10		PART NO. FX10B-168S-SV(93)	
DESIGNED : MT. ITANO		16.11.10		CODE NO. CL570-0254-0-93	
DRAWN : MT. ITANO		16.11.10		1/1	