



- NOTES: (b)
- FOR WAVESOLDERING (SOLDER BATH TEMPERATURE 260°C FOR 5SEC. AND SOLDER PREHEAT 100°C FOR 30SEC.)
  - METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
  - INSULATOR: HIGH TEMPERATURE PLASTIC UL 94 V-0; BLACK
  - CONTACTS: COPPER ALLOY; PLATING (SEE PART NO.):
    - PLEASE ADD A for GOLD FLASH over NICKEL (PREFERRED TYPE)
    - PLEASE ADD B for 20µm HARD GOLD over min. 50µm NICKEL
    - PLEASE ADD C for 30µm HARD GOLD over min. 50µm NICKEL
  - CAPACITANCE: 370pF ± 20%
  - DIELECTRIC WITHSTANDING VOLTAGE: 424 VDC
  - CONNECTOR IS PART MARKED: 241□10030X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm		scale: 2:1 (5:1)	
	date		name		material: SEE NOTES	
	drawn	07.05.2014	Heinrich		title: <b>D-SUB C-FILTER MALE</b> 25pos. SOLDER PIN STRAIGHT	
	appd.	07.05.2014	Henneboel			
	norm					
3 x b	A5200	07.05.2014	Heinrich	dwg no:	DIN-A3	
a	Original				sh: 1	
rev.	description	date	name			
				part no: (b) 241□10030X	(see note 4)	