



# 3M™ Strip Holder 5012 and 5012-L

## Instructions

### 1.0 General

The 3M™ Strip Holders 5012 and 5012-L are used to provide cable and pole identification when used in conjunction with 3M™ Lettering Systems.

Approximate size of the strip holders:

5012 - 3.1" x 10.5"

5012-L - 3.1" x 15.9"



## 2.0 Installation

- 2.1 Select the appropriate characters.
- 2.2 Using a 3M™ Scotch-brite™ Cleaning Pad 5008 (not included), scuff the shiny surface side of the strip holder.
- 2.3 Bend upper corner of number or letter to separate liner from adhesive.
- 2.4 Remove liner approximately half-way and fold or bend back.
- 2.5 Align character in the proper position. Contact upper portion of tab with the scuffed side of the strip holder. Remove remaining portion of liner and press tab into place. Repeat procedure to complete the lettering system.
- 2.6 Using a plastic squeegee, firmly press characters to surface.
- 2.7 For cable mounting, thread a black weather resistant cable tie (truck stock) through the two largest holes at both ends of strip holder as shown in Figure 1. Secure to the cable and snip off excessive tie length.
- 2.8 For pole mounting, nail the strip holder to the pole using the six holes on the outside edges as shown in Figure 2.



Figure 1

Inner holes and cable ties may also be used for mounting to cable.



Figure 2

Use outer holes and nails for mounting on poles.

3M and Scotch-brite are trademarks of 3M Company.

### Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

### Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



### Communication Markets Division

6801 River Place Blvd.  
Austin, TX 78726-9000  
1-800-426-8688  
www.3MTelecommunications.com

Please Recycle. Printed in USA.  
© 3M 2011. All Rights Reserved.  
78-0013-4897-4-A